



E408-100

Precision, Plate Mounted 100W Attenuator



E408-100

Features

- 1.5 dB Steps for Sound Masking and Other Precision Applications
- 100 Watt Power Handling
- Rack or Plate Mounting

General Description

Specially designed for attenuation in masking and sound reinforcement systems where fine tuning of level control is required. Employs a ten-position, non-shorting rotary switch without stop. Attenuation rate is 1.5dB per step. (All other specifications are the same as the AT Series including the UL listing.)

Specifications

Height	4½" (114.3mm)
Width	2¾" (69.9mm)
Depth	2⅝" (66.7mm)
Shipping Weight	1.00 lb (0.45 kgs)
Plate Size	1-gang
Plate Type	Stainless Steel
Power Rating	100 Watts
Total Attenuation	15dB
UL Listed/Standard	813, 2043

Architect and Engineer Specifications

Plate mounted wall attenuator shall be Atlas Sound model E408-100. Attenuator shall be capable of handling up to 100W of RMS power. Attenuator shall have a ten position, non shorting rotary switch design without stops. Total attenuation shall be 15dB with each position adjustment being 1.5dB. Unit shall be both UL813 and UL2043 rated. Attenuator shall be able to be rack mounted or wall mounted with included stainless steel, single gang wall plate. Dimensions shall be 2¾"W x 2⅝"D x 4½"H (69.9mm x 66.7mm x 114.3mm).